



122HF GREENLINE PLUS (1SN / R1AT)




Tuotenro	Sisä-Ø tuuma	Holkki HITRAK	Puristusmitta mm	Työpaine bar
122HF-04	1/4	SSP5-04	17,50	225
122HF-06	3/8	SSP5-06	20,50	180
122HF-08	1/2	SSP5-08	23,00	160
122HF-10	5/8	SSP5-10	25,70	130
122HF-12	3/4	SSP5-12	30,50	105
122HF-16	1	SSP5-16	38,00	88

221T SLIMLINE PLUS (2SC)




Tuotenro	Sisä-Ø tuuma	Holkki HITRAK	Puristusmitta mm	Työpaine bar
221T-04	1/4	SSP5-04	17,60	400
221T-06	3/8	SSP5-06	20,20	330
221T-08	1/2	SSP5-08	23,30	275
221T-12	3/4	SSP5-12	30,90	215

241T SUPER SLIMLINE HI-TUFF / 261E HYPERCOLD



Tuotenro	Sisä-Ø tuuma	Holkki HITRAK	Puristusmitta mm	Työpaine bar
241T/261E-04	1/4	SSP5-04	17,60	420
241T/261E-06	3/8	SSP5-06	20,50	350
241T/261E-08	1/2	SSP5-08	23,60	310
241T/261E-10	5/8	SSP5-10	26,20	280
241T/261E-12	3/4	SSP5-12	30,90	240
241T/261E-16	1	SSP5-16	38,30	210

222HF GREENLINE PLUS (2SN / R2AT)



Tuotenro	Sisä-Ø tuuma	Holkki HITRAK	Puristusmitta mm	Työpaine bar
222HF-04	1/4	SSP5-04	18,40	400
222HF-06	3/8	SSP5-06	21,50	330
222HF-08	1/2	SSP5-08	23,80	275
222HF-10	5/8	SSP5-10	26,60	250
222HF-12	3/4	SSP5-12	31,60	215
222HF-16	1	SSP5-16	38,90	165

730G POWERTRAK MSHA (4SP)



Tuotenro	Sisä-Ø tuuma	Holkki HITRAK	Puristusmitta mm	Ulkokuorrinta mm	Työpaine bar
730G-04	1/4	SSP3-04	19,60	25,0	450
730G-06	3/8	SSP3-06	23,70	25,0	445
730G-08	1/2	SSP3-08	26,80	27,0	415
730G-10	5/8	SSP3-10	30,40	28,0	350
730G-12	3/4	SSP3-12	34,70	33,5	380
730G-16	1	SSP3-16	42,40	38,0	320

790G POWERTRAK MSHA (4SH)



Tuotenro	Sisä-Ø tuuma	Holkki INTERLOCK	Puristusmitta mm	Ulkokuorrinta mm	Sisäkuorrinta mm	Työpaine bar
790G-12	3/4	SSP4-12	34,10	42,0	16,0	420
790G-16	1	SSP6-16	42,20	60,0	20,0	380
790G-20	1 1/4	SSP4-20	49,50	62,0	20,0	350
790G-24	1 1/2	SSP4-24	58,00	82,0	27,0	290
790G-32	2	SSP4-32	72,50	85,0	27,0	250