

POWERFLEXBIO-LETKUILLE

POWERFLEXBIO 4000



Tuotenro	Sisä-Ø tuuma	Holkki HITRAK	Kuorinta-pituus mm	Puristus-mitta mm	Työpaine bar
8V7AA-12	3/4	H1200204-120000	-	35,7	280
8V7AA-16	1	330000-16-16	37,0	40,9	280

POWERFLEXBIO 5000



Tuotenro	Sisä-Ø tuuma	Holkki HITRAK	Kuorinta-pituus mm	Puristus-mitta mm	Työpaine bar
8V2AA-10	5/8	330000-10-10	28,0	28,9	350
8V2AA-12	3/4	440000-12-12	33,0	33,3	350
8V2AA-16	1	330000-16-16	37,0	41,2	350

		INTERLOCK	sisä/ulko		
8V2AA-20	1 1/4	170000-20-20I	22,0 / 74,0	49,7	350
8V2AA-24	1 1/2	180000-24-24	22,0 / 81,0	63,2	350
8V2AA-32	2	180000-32-32	29,0 / 85,0	80,6	350

POWERFLEXBIO 5000 PLUS



Tuotenro	Sisä-Ø tuuma	Holkki POWERTRAK	Kuorinta-pituus mm	Puristus-mitta mm	Työpaine bar
8V9AA-16	1	190000-16-16	44,0	42,6	380

		INTERLOCK	sisä/ulko		
8V9AA-16	1	170000-16-16I	17,0 / 65,0	42,0	380

POWERFLEXBIO 6000



Tuotenro	Sisä-Ø tuuma	Holkki HITRAK	Kuorinta-pituus mm	Puristus-mitta mm	Työpaine bar
8V3AA-04	1/4	440000-04-04	19,0	18,3	450
8V3AA-06	3/8	440000-06-06	19,0	22,0	445
8V3AA-08	1/2	330000-08-08	25,0	26,3	420

		POWERTRAK			
8V3AA-12	1	190000-12-12	37,0	34,5	420

		INTERLOCK	sisä/ulko		
8V3AA-10	5/8	180000-10-10	15,0 / 50,0	31,7	420
8V3AA-12	3/4	170000-12-12I	15,0 / 52,0	34,0	420
8V3AA-16	1	170000-16-16I	17,0 / 65,0	42,0	420
8V3AA-20	1 1/4	180000-20-20	21,5 / 74,0	55,6	420
8V3AA-24	1 1/2	180000-24-24	22,0 / 81,0	63,2	420